

# STRIKE Array 2



## SPECIFICATIONS

### Optical

- Light Source: 96 LED (WW) 1.33 W, (2.2 A), 2700 K, 50,000 hours life expectancy
- Light Source: 10 LED (Amber) 2.63 W, (.750 A), 50,000 hours life expectancy
- Color Temperature (at full): 2792 K
- CRI: 92.9
- TLCI: 91
- Beam Angle: 60.3°
- Field Angle: 99°
- Illuminance (total): 360 lux @ 5 m
- Selectable PWM: 600 Hz, 1,200 Hz, 2,000 Hz, 4,000 Hz, 25,000 Hz

### Dynamic Effects

- Dimmer: Electronic
- Strobe Rate: 0 to 25 Hz
- Dim Modes: 4
- Built-in Automated Programs: Yes

### Optional Accessories

- Professional Clamps: CTC-50HC, CTC-50HCN
- Seetronic Powerkon power linking cables
- 5-pin IP or Non-IP DMX Cables
- STRIKE Array 2

## FEATURES

- Intense 2 pod blinder/strobe rated IP65 for all-weather use
- Emulated "red shift" to mimic incandescent fixtures perfectly.
- Individual pan (or tilt, depending on mount orientation) of each head to allow for directional adjustment of light output.
- Innovative interlocking system to connect multiple Strike Array 2s and Strike Array 4s together.
- Multiple mounting locations with ¼ turn adaptors for creative and convenient rigging options
- 16-bit dimming control for smooth, perfect fades
- Strobe functionality for high-impact effects on the fly
- Easy to use OLED display
- Adjustable Pulse Width Modulation (PWM) and RDM (Remote Device Management) for added flexibility

## Construction / Physical

- Dimensions: 18.5 x 10.4 x 6.3 in (469 x 264.5 x 161 mm)
- Dimensions (shipping size): 20.7 x 8.5 x 12.8 in (525 x 215 x 325 mm)
- Weight: 17.6 lb (8 kg)
- Weight (shipping weight): 21.6 lb (9.8 kg)
- Exterior Color: Black
- Housing Material: Aluminum die-cast

## Connections

- Power Connection: Edison (Local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Power Output: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP65 XLR
- Cable Length (power): 5 ft (1.5 m)

## Control

- Control Protocol: DMX, RDM

- DMX Channels: 1, 2, 3, 4, 5, or 8

## Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power Linking: 11 units @ 100 V; 13 units @ 120 V; 22 units @ 208 V; 24 units @ 230 V; 25 units @ 240 V
- Power and Current: 124 W, 1.24 A @ 100 V, 60 Hz [3.1 A inrush]
- Power and Current: 123 W, 1.04 A @ 120 V, 60 Hz [1.8 A inrush]
- Power and Current: 127 W, 0.61 A @ 208 V, 60 Hz [1.9 A inrush]
- Power and Current: 129 W, 0.56 A @ 230 V, 50 Hz [3.8 A inrush]
- Power and Current: 130 W, 0.54 A @ 240 V, 50 Hz [1.2 A inrush]
- Power and Current (resting): 3 W, .021 A @ 100 V, 60 Hz
- Power and Current (resting): 4 W, .029 A @ 120 V, 60 Hz
- Power and Current (resting): 7 W, .040 A @ 208 V, 60 Hz
- Power and Current (resting): 9 W, .040 A @ 230 V, 50 Hz
- Power and Current (resting): 10 W, .044 A @ 240 V, 50 Hz

## Certifications / Qualifications

- CE, MET
- IP Rating: IP65, temporary outdoor/wet use, with pressure equalizing M12 GORE valve
- Temperature (Ambient): -4 °F to 113 °F (-20 °C to 45 °C)

## What's Included

- Strike Array 2
- Seetronic Powerkon IP65
- Omega bracket with mounting hardware
- Warranty Card
- Quick Reference Guide or User Manual