

TECHNICAL SPECS

- ▶ **Type** Analogue
- ▶ **Channels** 6 + 2
- ▶ **EQ**
Channel 1-4, 4-Band EQ
Channel A-B, 3-Band Parametric EQ
- ▶ **USB Soundcards** Dual 24 Channel (12 in / 12 out)
Hi-Speed USB2.0 / Mac Class Compliant
32bit / 96kHz
MIDI over USB
- ▶ **Line Inputs** 4 x RCA (CH 1-4)
4 x 1/4" TRS (CH A-D) Mono/Stereo
- ▶ **Phono Inputs** 4 x RCA (CH 1-4)
LN/PH Switch for DVS
- ▶ **USB Inputs** 6 x USB (CH 1-4 + CH A – CH B)
- ▶ **Mic Input** 2 x XLR
- ▶ **Master Output** 1 x XLR (Balanced)
- ▶ **Master 2 Output** 1 x 1/4" TRS (Balanced)
- ▶ **Booth Output** 1 x 1/4" TRS (Balanced)
- ▶ **Record Output** 1 x RCA (Un-balanced)
- ▶ **Master Insert** 1 x 1/4" TRS
- ▶ **MIDI Out** 1 x 5-Pin DIN
- ▶ **Send/Return I/O**
2 x 1/4" TRS Send
4 x 1/4" TRS Return
1 x LN/Hi-Z Switch (SND1/RTNA)

- ▶ **Filter**
2 x VCF Filter
HPF / BPF / LPF
Adjustable Frequency & Resonance
Assignable CH 1-4 + CH A-B
CRUNCH (Controlled Harmonic Signal Distortion)
- ▶ **X-Link** 1 x RJ45
- ▶ **Headphones**
2 x 1/4"
2 x 3.5mm
Split Cue Monitoring
- ▶ **Channel Faders** 60mm VCA / Replaceable
- ▶ **Chanel Meters** 9 Segment LED
- ▶ **Channel Fader Curve** 3 Types
- ▶ **X-Fader** InnoFADER / 45mm VCA / Replaceable
- ▶ **X-Fader Curve** 3 Types
- ▶ **Earth Ground Terminals** x 2
- ▶ **Headroom** 20dB
- ▶ **AC Mains**
100 to 240V
AC 50/60Hz
Consumption 45W max
- ▶ **Mains Adaptor** 3 pin IEC socket
- ▶ **Height** 109mm / 4.3"
- ▶ **Width** 336mm / 13.25"
- ▶ **Depth** 410mm / 16.2"
- ▶ **Weight** 7kg / 15.4 lbs.